

## CLAIMS

1. A method for packaging products (3), such as candies,  
in a removable enclosure, wherein the products (3)  
5 are positioned on a first sheet (1) which is  
continuously moved in a transport direction, wherein  
the products (3) are covered by a second sheet (2)  
which is continuously moved in the same transport  
direction and which is aligned substantially plane-  
10 parallel to the first sheet (1), and wherein the  
first and second sheets (1,2) are sealed together  
near the outer edges of the individual products (3)  
or grouped products by a sealing device (10, 22, 16),  
characterised in that the sealing device comprises  
15 sealing ribs (12) extending substantially  
transversely to the transport direction on one side  
of the moving sheets (1, 2), wherein said sealing  
ribs (12) are being moved at the same speed as the  
sheets (1, 2) and the sealing ribs (12) seal the  
20 first and second sheets (1, 2) together in between  
the moving products (3).
2. The method according to claim 1, wherein the sealing  
device (10, 22, 16) comprises a rotating frame (10),  
25 the rotation axis of said frame (10) extending  
transversely to the transport direction, wherein said  
sealing ribs (12) extend from a coaxial cylindrical  
surface of said frame (10).
- 30 3. A method according to claim 1, wherein at least one  
of said sheets (2) is pre-shaped to fit at least  
partially around the products (3) before the sheet  
(2) comes into contact with the products (3).

4. A method according to claim 2, wherein said pre-shaping action is performed by a pre-shaping device (10, 11) comprising a first rotating shaping frame (10) on one side of the moving sheet (2) and a second rotating shaping frame (11) on the opposite side of the moving sheet (2), the rotation axes of both frames (10, 11) extending transversely to the transport direction of the sheet (2), wherein said frames (10, 11) comprise co-operating protruding shaping ribs (12, 13) extending substantially transversely to the transport direction, wherein the shaping ribs (12, 13) of both frames (10, 11) move between each other, and wherein said shaping ribs (12, 13) are being moved at the same speed as the pre-shaped sheet (2).
5. A method according to claim 3, wherein the first pre-shaping frame (10) is positioned such that it guides the pre-shaped film (2) towards the other moving sheet (1) while including the products (3).
6. A method according to any of the preceding claims 1 - 4, wherein the products (3) have an elongated form and are positioned transversely on the first moving sheet (1).
7. A method according to any of the preceding claims 1 - 5, wherein the sealing ribs (12) comprise ultrasonic welding means.
8. A method according to any of the preceding claims, wherein the sealed areas between the products (3) are

perforated or scored, such that the packaged products (3) stay attached to each other, but can be easily separated.

5 9. A device for packaging products (3), such as candies, comprising first transport means (8) for continuously moving a first sheet (1) in a transport direction, positioning means (4, 5, 6) for positioning the products (3) on the first sheet (1), second transport  
10 means (10) for continuously moving a second sheet (2) in the same transport direction in alignment substantially plane-parallel to the first sheet (1) while covering the products (3), and a sealing device (10, 22, 16) for sealing the first and second sheets  
15 (1, 2) together near the outer edges of the individual or grouped products (3), characterised in that the sealing device (10, 22, 16) comprises protruding sealing ribs (12) extending substantially transversely to the transport direction, and said  
20 sealing device (10, 22, 16) further comprises synchronizing means for moving said sealing ribs (12) at the same speed as the sheets (1, 2) while sealing the first and second sheets (1, 2) together in between the moving products (3).

25  
10. A method for packaging products (3), such as candies, wherein the products (3) are positioned on a first sheet (1) which is continuously moved in a transport direction, wherein the products (3) are covered by a  
30 second sheet (2) which is continuously moved in the same transport direction and which is aligned substantially plane-parallel to the first sheet (1), and wherein the first and second sheets (1, 2) are

sealed together near the outer edges of the individual grouped products (3) by a sealing device (10, 22, 16), wherein at least one of said sheets (2) is pre-shaped by a pre-shaping device (10, 11) to fit at least partially around the products (30) before the sheet (2) comes into contact with the products (3), characterised in that said pre-shaping device (10, 11) comprises a first rotating shaping frame (10) on one side of the moving sheet (2) and a second rotating shaping frame (11) on the opposite side of the moving sheet (2), the rotation axes of both frames extending transversely to the transport direction of the sheet (2), wherein said frames comprise co-operating protruding shaping ribs (12, 13) extending substantially transversely to the transport direction, wherein the shaping ribs (12, 13) of both frames (10, 11) move between each other, and wherein said shaping ribs (12, 13) are being moved at the same speed as the pre-shaped sheet (2).

11. A device for packaging products (3), such as candies, comprising first transport means (8) for continuously moving a first sheet (1) in a transport direction, positioning means (4, 5, 6) for positioning the products (3) on the first sheet (1), second transport means (10) for continuously moving a second sheet (2) in the same transport direction in alignment substantially plane-parallel to the first sheet (1) while covering the products (3), a sealing device (10, 22, 16) for sealing the first and second sheets (1, 2) together near the outer edges of the individual or grouped products (3), and a pre-shaping device (10, 11) for pre-shaping at least one of said

5 sheets (2) to fit at least partially around the products (3) before the sheet comes into contact with the products (3), characterised in that said pre-shaping device (10, 11) comprises a first rotating  
10 shaping frame (10) on one side of the moving sheet (2) and a second rotating shaping frame (11) on the opposite side of the moving sheet (2), the rotation axes of both frames (10, 11) extending transversely to the transport direction of the sheet (2), wherein  
15 said frames (10, 11) comprise co-operating protruding shaping ribs (12, 13) extending substantially transversely to the transport direction, wherein the shaping ribs (12, 13) of both frames are movable between each other, and said pre-shaping device (10, 11) further comprises synchronizing means for moving  
20 said shaping ribs (12, 13) at the same speed as the pre-shaped sheet (2).

12. An array (19) of packaged products (3), such as  
20 candies, comprising two sheets (1, 2) which are sealed together and enclose said products (3) or groups of products, wherein the sealed areas between the products (3) are weakened, such that the packaged products (3) can be easily separated, characterised  
25 in that one of said sheets (1) is a substantially flat relatively rigid board or film and the other sheet (2) is a relatively flexible foil shaped to fit at least partially around the products (3).

30 13. An array (19) of products (3) according to claim 11 or 12, wherein the products (3) have an elongated form and are positioned transversely with respect to the sheets (1, 2).

14. An array (19) of products according to claim 13,  
wherein the sides of the sealed sheets (1, 2)  
extending from the outer ends of the products (3) are  
5 bend in order to give the array (19) rigidity in its  
longitudinal direction.